





DIMENSIONS

- Overall Height: 12' 7"
- Overall Length: 49' 10"
- Wheelbase: 255"

CHASSIS

- Spartan Gladiator LFD 5" Raised Roof
- Front Axle GAWR: 24.000 lbs
- Rear Axle GAWR: 62,000 lbs
- Cummins X15 605 HP Engine
- Allison 4000 EVS Transmission
- Seating Capacity: 4
- **Advanced Protection System**
- **Advanced Climate Control**
- 68 Gallon Fuel Tank
- Michelin Tires
- 24" Severe Duty Front Bumper
- **Bostrom Seats**
- Internal EMS and Tool Storage
- Alcoa Aluminum Wheels with DuraBright Finish

PUMP & PLUMBING

- Waterous CSU 2000 GPM Pump
- 300 Gallon Water Tank
- (1) 2.5" Left Side Inlet
- (2) 2.5" Left Side Discharge
- (1) 2.5" Right Side Discharge
- (1) 4" Right Side Master Discharge
- (2) 1.75" Crosslays
- (1) 2.5" Crosslay
- (1) 2.5" Front Bumper Discharge
- Booster Reel
- Akron 3" Tank to Pump
- 2" Tank Re-Fill Line

AERIAL

- 100' Rear Mount Platform Structure
- Front and Rear "H" Style Stabilizers
- Whelen Pioneer Tracking and Tip Scene Lights
- 4500 PSI Breather Air System
- Parapet Ground Ladder Attachment
- Rappelling Arm 500# Limit
- **TFT Electric Monsoon Monitor**
- TFT Master Stream 2000 GPM Monitor
- TFT Valve Under Monitor with Left Hand Discharge
- Stokes Basket Storage on Base Section
- 14' Aluminum Roof Ladder on Base Section
- 10' New York Roof Hood in Fly Section

BODY

- 100" Wide 1/8" Thick Aluminum Body
- On-Scene LED Compartment Lighting
- Duo-Safety Ladder Package:
 - (1) 10' Aluminum Attic Ladder
 - (1) 14' Aluminum Roof Ladder
 - (1) 16' Aluminum Roof Ladder
 - (1) 28' 2-Section Aluminum Ladder
 - (1) 35' 3-Section Aluminum Ladder
- (2) 12' National Hooks
- (2) 6' New York Roof Hooks
- (2) 8' New York Roof Hooks
- Whelen Warning Light Package
- Left, Right, and Rear Camera System
- On-Scene & Austin FDR Slide-Out Trays
- **PAC Tool Boards**
- FireTech Scene Lighting

